

COMPOSITION 100% P.T.F.E. DUPONT 65/N.

TECHNICAL FEATURES

CHEMICALLY INERT.

DENSITY: 0,95 gr/cm³.

It is inodorous and tasteless.

Soft and e flexible guarantees a perfect tightness on irregular or defective areas.

RESISTANCES

PRESSURE: 210bar.

TEMPERATURE: -200°C +280°C, up to 315°C.

CHEMICAL: pH 0-14; it is resistant to all chemical products and solvents, exception for alkaline materials in particular conditions (as Du Pont literature).

PROPERTIES

INSURES a perfect tightness of long life on flanges of pumps and pressers , of industrial and chemical equipments, of pipes and steam's conduits, hydrocarbons, weapon fluids in general and oxygen.

Use on conduits, autoclaves and metal reservoirs, in chemical and food industry, for raised forces of tightening.

INSTRUCTIONS

Degrease, clean and dry the areas to connect; remove the protecting strip from the adhesive surface and position the gasket; conclude the operation with the intercrossed superimposition of the extremity or connecting the same ones with oblique cut. Proceed with the gradual and intercrossed clamping of the bolts. If necessary regulate the tightening on the exercise temperature. In the presence of fragile areas or reduced forces of tightening, the cut oblique connection is preferable.

**CERTIFIED PRODUCT TÜV TESTING STANDARD MUC - KSP - A 066
ACCORDING TO THE REGULATIONS OF THE FDA and WRC.**

WRAPPED IN BOBBINS STANDARD DIMENSIONS (width x length x thickness)

3mm x 1.5mm x 50mt	12mm x 4mm x 10mt	25mm x 5mm x 5mt
5mm x 2mm x 50mt	14mm x 4mm x 10mt	25mm x 8mm x 5mt
7mm x 2.5mm x 25mt	17mm x 6mm x 10mt	25mm x 10mm x 5mt
10mm x 3mm x 10mt	20mm x 7mm x 5mt	30mm x 10mm x 5mt
10mm x 5mm x 10mt	20mm x 10mm x 5mt	40mm x 5mm x 5m